

MODEL # WATER2ATTC



P.O.BOX 100
CERES, CA 95307
www.west-mark.com

PHONE: (209) 537-4747
TOLL FREE: (800) 692-5844
FAX: (209) 537-1753

GENERAL

The following equipment shall be a new dust control tank truck.

PRODUCT: Non-potable water.

PRODUCT WEIGHT: 8.35 lbs./gallon.

VESSEL CODE: Non-Spec.

TANK OPERATING PRESSURE: Atmosphere.

TANK OPERATING TEMPERATURE: 125° F maximum

INTENDED AREA OF OPERATION: Specify _____.

INTENDED USE: Highway and Unimproved roads.

CHASSIS

New Freightliner model M2 106 conventional cab, 2-door chassis:

BRAKES: Air type
DRIVE: 4 X 2
GVWR: 33,000 lbs
Front Axle: 12,000 lbs Capacity
Rear Axle: 21,000 lbs Capacity, Spring Suspension
Engine: Cummins ISB 250 HP and 660 lb/ft torque
Transmission: Allison 3500 RDS automatic

- Cab color to be White
- Battery disconnect switch
- Maintenance free batteries
- Remote mounted positive & negative posts for jumpstart
- Vertical tailpipe mounted at RH side
- Coolant rated to -34F
- Engine block heater
- Quick disconnect fitting with tire inflation kit.
- Front tow hooks, eye(s), or pin (application varies based GVWR)
- LH and RH grab handles
- Air horn
- Electric horn(s)
- Daytime running lights
- LH and RH convex mirrors mounted under primary mirrors
- Heater, defroster, and air conditioner
- One (1) each 12V power supply in dash
- Speedometer/Odometer capable of displaying in both miles and kilometer, with trip and hour meter.
- Adjustable tilt and telescoping steering column
- Back-up alarm
- AM/FM/WB radio with Bluetooth and Auxiliary inputs
- Cab suspension - Air Ride
- Air driver and fixed passenger seats
- Heated mirrors (flat and convex)
- Heated fuel/water separator

MODEL # WATER2ATTC

- Mud and snow tires on rear axle(s)
- Steel wheels
- Towing extended/roadside service warranty, 1 year/unlimited miles/km, \$550 cap (U.S. Domestic only)

BODY

- 2,000 Gallon Non-Potable water painted steel tank.
- Heads, 3/16" A36
- Baffle(s) 3/16" A36.
- Baffle(s), Longitudinal 3/16" A36
- U-shaped subframe.
- Doubler plate, 3/16" A36
- Rubber pads between tank and frame.
- Tank Mounts, four (4).
- Manway, 24" circular
- Vortex Breaker, plate w/ screen
- Hydrant Fill, 2.5" w/ swivel swing spout
- Sight Gauge(s), two (2); one at rear and one at front w/ shut-offs.
- Ladder, one (1) rear mounted w/ handrails.
- Fenders, two (2) bonnet style tandem axle.
- Walkway, non-skid top of tank.
- Light Kit, D.O.T. L.E.D.
- Conspicuity tape, D.O.T.
- Mud flaps, rear mounted.
- Paint, tank to be WHITE to match cab.
- Pump, water 750 gpm rated.
- PTO, air shift
- Driveline, 1000 series PTO shaft
- Controls, PTO Cab mounted.
- Pump plumbing, carbon steel.
- All plumbing components welded with groove couplers.
- Distribution manifold.
- Air valves for spray heads cab controlled
- Front Sprayers, two (2) with adjustable fan heads.
- Rear Sprayers, two (2) with adjustable fan heads.
- Side spray left hand side, duck bill with manual up/down operation
- Discharge, 1.5" ball valve driver's side.
- Control Switches, cab mounted.
- Rear in-frame storage area with lid.
- Bumper, rear per D.O.T.
- Paint, frame and plumbing components painted BLACK.
- Low point drains installed in all plumbing.

Warranty, unit shall be free from defects in material and workmanship for a period of ONE (1) year.

FOB: Phoenix, AZ