

DOT 407/412

Hazardous Vacuum Trailer



Product Focus

The DOT 407/412 Hazardous Vacuum Trailer is your top choice for safely transporting hazardous materials. Meeting stringent DOT 407/412 standards, it excels in handling volatile liquids and chemicals with full vacuum capability with spill-free loading and unloading. Ideal for industrial and environmental cleanup, it ensures compliance and environmental protection.

Product	Capacity	Tank Material
Hazardous Material	5,500 Gallons	T-316 Stainless Steel

Key Product Specifications

- **FRONT AXLE LIFT KIT:** Hendrickson to lift Intraax Suspension with air control kit
- **MANHOLE:** Three 20" BETTS 8350 manholes, T316L stainless steel, 50 psi MAWP, Viton gasket.
- **LEVEL GAUGE:** Stainless steel float ball assembly, laser-etched dial rear head location.
- **LADDER/HANDRAILS:** Aluminum tubular ladder, slip-resistant steps, and platform, guard rails, 18"-22" from the ground.
- **OUTLET:** 6" 90° elbow outlet, Clearflow sliding gate valve, 6" Camlock adapter and cap.
- **RISER PIPE LOAD LINE:** 4" stainless steel riser pipe, Clearflow sliding gate valve, 4" Camlock adapter and cap.
- **PUMP:** Fruitland 870 series, 501 CFM vacuum/pressure pump, at landing legs
- **HYDRAULIC SYSTEM:** Stainless steel lines with controls
- **CABINETS:** Stainless steel cabinet (30" W x 24" H x 24" D), lockable, drainage holes, front of rear subframe.